



## DAS-G Series

### Product Description

ATCA-compliant, 3U / 6U / 16U and other standard chassis, including 3U2 slot, 6U6 slot, 16U14 slot.

### Product Features

- Advanced system architecture, using standardized, modular design concept, with a wealth of scalability and flexibility can be customized, with the needs of the expansion of input and output modules and business processing module;
- Highly integrated, scalable, ATCA equipment specification, can be placed directly on standard 19-inch racks, with 14-slot chassis with maximum wire speed handling 960GE data and support multi-chassis cluster expansion with rich expansion interfaces;
- Support serial port management, Telnet remote management, SSH encryption management and SNMP simple network management, support remote upgrade maintenance.

### Product Specification

Types	Chassis model	Power supply specification	Number of business cards
3U 2 slot chassis	DAS-G-20-AA-13	Dual -48VDC power supply	2 Service Cards
	DAS-G-20-BB-13	Dual 220VAC powered	
6U 6 slot chassis	DAS-G-42-AA-16	Dual -48VDC power supply	4 Service Cards + 2 Switch Cards
	DAS-G-42-BB-16	Dual 220VAC powered	
16U 14-slot chassis	DAS-G-122-BB-116	Dual -48VDC power supply	12 Service Cards + 2 Switch Cards
	DAS-G-122-AA-116	Dual 220VAC powered	Or 10 Service Cards + 4 Switch Cards